K-RCS114 Round Cable Stripper

Round cables of 4.5–29 mm diameter — ring, spiral or longitudinal cuts, at the end or mid-span, at a blade depth you set.

A round cable jacket has to be scored evenly all the way round, at exactly jacket depth — too shallow and it will not part, too deep and the blade reaches what the jacket was protecting. The K-RCS114 replaces feel with two set mechanics: a spring-loaded brace that wedges the cable against the blade at constant pressure, and a depth setting dialed in on the knob before the cut starts. It covers round cables of 4.5–29 mm.



K-RCS114 from the side — brace closed over the head

Key Features

- Strips round cables from 4.5–29 mm — the diameter stated in full, so the tool is matched to the cable before it is ordered, not after it arrives
- Spring-loaded cable brace wedges the cable firmly against the blade, so the cut runs at a controlled, even depth all the way round — no wandering score line, no second pass
- Blade depth is set on the knurled knob at the head: dial it to the jacket thickness in front of you and the blade cuts the jacket only, stopping above the shield, the strength members and the fibers
- Three cuts from one tool: rotate it for a ring cut, draw it along for a longitudinal slit, or walk it in a spiral — the spiral cut opens a mid-span window without ringing the cable through
- Works at cable ends and mid-span alike, on PE, PVC and rubber jackets — the everyday sheaths of round fiber and copper cables
- 138 mm ergonomic handle at about 100 g, with a replaceable blade — it lives in a pocket or a kit pouch, with no setup and nothing to charge
- Need the other half of the range? The K-RCS158 covers 19–40 mm — together the two sizes strip round cables from 4.5 mm to 40 mm
- Private labeling made to your requirements — labels with your logo, part numbers and barcodes on the inner boxes and outer cartons, ready for your warehouse

Specifications

Cable diameter	4.5–29 mm
Jacket materials	PE, PVC, rubber and other jacket materials
Cut types	Radial (ring), spiral and longitudinal — at cable ends and mid-spans
Cable brace	Spring-loaded — wedges the cable against the blade for a controlled cut
Blade depth	Adjustable — knurled knob at the head
Blade	Replaceable
Handle	Ergonomic rounded handle, black
Length	138 mm
Weight	Approx. 100 g

One More View

Angled, the tool shows how the brace folds down over the cable at the head, with the depth knob clear of the work — the position it is in for every cut.



Angled view — the brace folds over the cable at the head

In Use

Set the depth on a scrap end of the same cable first: turn the knob until the blade just parts the jacket on a test ring. Seat the cable in the brace and rotate the tool for the ring cut, then draw it along for the longitudinal slit — ring and slit meet and the jacket section lifts off in one piece. For a mid-span window, ring at both ends and run a shallow spiral between the rings. Brush jacket crumbs out of the brace after a session, and check the depth setting whenever the cable type changes.

OEM & Private Label

The K-RCS114 is supplied in neutral, unbranded stock as standard. Private labeling is made to your requirements — labels with your logo, part numbers and barcodes on the tools, the inner boxes and the outer cartons, so the goods arrive ready for your warehouse. Custom barcode & contract labeling is applied to every inner box and outer carton to your receiving specification.